

Installation of a Tilt-before-Turn (TbT) handle

Installing a Tilt-before-Turn (TbT) handle is slightly different from a standard handle because a TbT handle has a direction. Before installation it needs to be set in the right position depending on the opening direction of the window.

Installation instruction:

Instruction	Image
Use the square pin of the handle to put the window in from locked to tilt position . To do that, rotate by 90 degrees. Check to see if the window is really in tilt position.	
The TbT handle has a "Turn Mode Unlocked" and a "Turn Mode Locked" state.	Turn Mode Unlocked Turn Mode Locked
See on right.	
Put the handle in the "Turn Mode Locked" state with the key that is supplied with the handle.	
If you cannot turn the key into the correct locked position, hold the base of the handle and turn the handle by 180 degrees. Try to turn the key again.	
Hold the handle vertical as shown on above.	Use for:
Hold the base of the handle and turn the handle left or right 90 degrees to one of the positions shown on the right.	Window with hinges on left, handle on right
You should not be able to turn the handle more than 90 degrees.	
Make sure you choose the correct way that corresponds to the opening direction of your window. The handle should point towards the hinge side of the window.	Window with hinges on right, handle on left
The handle should now look like shown on the right.	



Tilt-before-Turn handle installation

Instruction	Image
Install the handle with the handle horizontal.	Window with hinges on left, handle on right
	Window with hinges on right, handle on left
You should now be able to turn the handle only between Locked state and Tilt state.	
Finish by unlocking the handle with the provided key. Now you should be able to turn the handle vertical upward and thus use the Turn mode of the window.	
If the tilt-before-turn functionality does not work as expected, put the window in tilt position, uninstall the handle, turn the base by 180 degrees and re-install the handle.	